

# 油壓刀把 HYDRAULIC CHUCK



Including pull stud and balancing.  
附拉桿，動平衡。

Balancing / 動平衡	Dimensions / 尺寸標示
<p>Option / 選配</p> <p><b>G2.5</b></p> <p>Max.30,000 RPM Or U ≤ 1gmm</p>	

page.118

page.115

page.144



Collet  
筒夾



Pull Stud  
拉桿



Screw  
調整螺絲

Order No. 訂購編號	▲ ød	ød1	L	L1	L2	Tool Clamping Depth L3 刀具夾持深度	Collet 筒夾	Pull Stud 拉桿	Screw 調整螺絲
ISO30	6	26	60	24.5	40.9	31~36	-	PI30T-1	HY06-M5
	8	28	60	25.5	40.9	31~36	-	PI30T-1	HY08-M6
	10	30	75	35.5	55.9	35~40	-	PI30T-1	HY08-M6
	12	32	75	40	55.9	39~45	HY12-C	PI30T-1	HY08-M6

Remarks / 備註

- 直接夾持精度 Direct Clamping
- 刀具柄徑公差 h6( h6 Tooling Diameter Tolerance)
- 若需出水型刀把，請參考 page.26 選用說明

Applications / 應用



Drilling  
鑽孔



Reaming  
銜孔



Endmilling  
銑削