

THER 小徑刀把 THER SLIM COLLET CHUCK



5 μm
RUN-OUT
HIGH PRECISION

| Balancing / 動平衡 | Dimensions / 尺寸標示 |
|---|-------------------|
| <p>G6.3 Max.25,000 RPM Or U ≤ 1gmm</p> <p>Option / 選配 G2.5 Max.25,000 RPM Or U ≤ 1gmm</p> | |

| Order No. 訂購編號 | Range 夾持範圍 | Range 夾持範圍 | $\phi d1$ | $\phi d2$ | L | L1 | L2 | Tool Clamping Depth L3 刀具夾持深度 | page.146 | page.144 | page.120 | page.149 |
|-------------------|---------------|---------------|-----------|-----------|-----|-----|-------|----------------------------------|------------|---------------|--------------|--------------|
| | | | | | | | | | Nut 螺帽 | Screw 調整螺絲 | Collet 筒夾 | Wrench 扳手 |
| HSK50A | THER11-100 | 1.0~7.0 | 16 | 20.6 | 100 | 74 | 69.2 | 19~48 | CAP-THER11 | ER-M8 | ER11-HP | PHS-20-RO160 |
| | THER16-100 | 1.0~10.0 | 22 | 26.2 | 100 | 74 | 69.2 | 29~58 | CAP-THER16 | ER-M11 | ER16-HP | PHS-20-RO220 |
| HSK63A | THER11-100 | 1.0~7.0 | 16 | 20.3 | 100 | 74 | 66.3 | 19~48 | CAP-THER11 | ER-M8 | ER11-HP | PHS-20-RO160 |
| | THER11-130 | 1.0~7.0 | 16 | 22.9 | 130 | 104 | 96.3 | 19~48 | CAPTHER11 | ER-M8 | ER11-HP | PHS-20-RO160 |
| | THER11-160 | 1.0~7.0 | 16 | 25.5 | 160 | 134 | 126.3 | 19~48 | CAP-THER11 | ER-M8 | ER11-HP | PHS-20-RO160 |
| | THER16-100 | 1.0~10.0 | 22 | 26.2 | 100 | 74 | 69.2 | 29~58 | CAP-THER16 | ER-M11 | ER16-HP | PHS-20-RO220 |
| | THER16-130 | 1.0~10.0 | 22 | 28.8 | 130 | 104 | 99.2 | 29~58 | CAP-THER16 | ER-M11 | ER16-HP | PHS-20-RO220 |
| | THER16-160 | 1.0~10.0 | 22 | 31.4 | 160 | 134 | 129.2 | 29~58 | CAP-THER16 | ER-M11 | ER16-HP | PHS-20-RO220 |

Remarks / 備註

- 需配合 3μ HP 筒夾 With 3μ HP Grade Collet
- 若需搭配中心出水管，請參考 page.145 規格表
- 若需出水型刀把，請參考 page.26 選用說明
- 筒夾夾持為一對一整數值

Applications / 應用

