

CR 標準型熱縮刀把

CR STANDARD SHRINK FIT CHUCK



Balancing / 動平衡	Dimensions / 尺寸標示
<p>G6.3 Max.30,000 RPM Or U ≤ 1gmm</p> <p>Option / 選配 G2.5 Max.30,000 RPM Or U ≤ 1gmm</p>	

page.144



Order No. 訂購編號		ød	ød1	ød2	L	L1	L2	Tool Clamping Depth L3 刀具夾持深度	Screw 調整螺絲
HSK32E	CR04-060	4	15	20	60	40	31.8	min18	-
	CR06-070	6	21	26	70	50	31.8	21.5~31.5	HY06-M5
	CR08-070	8	21	26	70	50	31.8	25.5~35.5	HY08-M6
	CR10-080	10	24	26	80	60	44.7	31.5~41.5	HY08-M6
HSK40E	CR04-060	4	15	20	60	40	31.8	min18	-
	CR06-080	6	21	27	80	60	34.3	21.5~31.5	HY06-M5
	CR08-080	8	21	27	80	60	34.3	25.5~35.5	HY08-M6
	CR10-080	10	24	32	80	60	47	31.5~41.5	HY08-M6
HSK50E	CR04-060	4	16	21.2	60	34	-	min18	-
	CR04-080	4	16	23	80	54	34.3	min18	-
	CR06-080	6	21	27	80	54	34.3	21.5~31.5	HY06-M5
	CR08-080	8	21	27	80	54	34.3	25.5~35.5	HY08-M6
	CR10-085	10	24	32	85	59	47	31.5~41.5	HY08-M6
	CR12-090	12	24	32	90	64	47	36.5~46.5	HY14-M8
CR16-095	16	27	34	95	69	40.7	39.5~49.5	HY18-M12	

Remarks / 備註

- 刀具柄徑公差 h6(h6 Tooling Diameter Tolerance)
- 若需搭配中心出水管，請參考 page.145 規格表
- 若需出水型刀把，請參考 page.26 選用說明

Applications / 應用



Drilling
鑽孔



Reaming
鉸孔



Endmilling
銑削